

(12) UK Patent Application (19) GB (11) 2 319 834 (13) A

(43) Date of A Publication 03.06.1998

(21) Application No 9622562.8

(22) Date of Filing 30.10.1996

(71) Applicant(s)
Sumitomo Rubber Industries, Ltd

(Incorporated in Japan)

6-9 3-chome, Wakinohama-cho, Chuo-ku, Kobe-shi,
Hyogo-ken, Japan

(72) Inventor(s)
Masahide Onuki
Satoru Kinuhata
Yuichi Takeuchi
Yoshiaki Miyamoto
Tetsuo Yamaguchi

(74) Agent and/or Address for Service
Carpmaels & Ransford
43 Bloomsbury Square, LONDON, WC1A 2RA,
United Kingdom

(51) INT CL⁶
G01P 3/36, A63B 69/36


(52) UK CL (Edition P)
G1A AA3 AEDX AR7 AT26 AT3
U1S S1155

(56) Documents Cited
GB 2288662 A EP 0704715 A1 EP 0554978 A2
US 5226660 A US 4158853 A US3630601 A

(58) Field of Search
UK CL (Edition O) G1A AAJX AEAX AEDX AEJX AEX
INT CL⁶ A63B 69/00 69/36 69/38, G01P 3/36 3/38
3/40 3/64 3/68, G01S 11/12
Online database: WPI

(54) Measurement of rotation speed of a flying object

(57) A rotation speed measuring machine for a flying globe B, such as a golf ball, has a device 10 projecting light on a measurement area A which includes the expected flying route of the globe B after the globe has been hit at a hitting position, a device 20 which receives light reflected from the globe in the measurement area A and which outputs a signal according to the reflected light fluctuations, and a means 30 for determining the rotational speed from the output signal of the light receiving device 20. A mark M having a reflectance different from that of the basic surface texture is placed on part of the surface of the globe B, eg by painting opposite quarter segments black. By detecting the period or frequency of fluctuations in the reflected light, the spin of the globe B may be measured around the highest point of the flight locus.



GB 2 319 834 A

1/5
FIG. 1




FIG. 2 (A)




FIG. 2 (B)






FIG. 3

TEST No.	LIGHT SOURCE	DISTANCE (m)	POSITION	INTENSITY OF ILLUMINATION (Lx)	ROTATIONAL SPEED (rpm)	MEASURED VALUE
1	DC	30	MID	70	9000	INCOMPLETE WAVE FORM
2	THE SAME AS ABOVE	THE SAME AS ABOVE	THE SAME AS ABOVE	100	9000	8960
3	THE SAME AS ABOVE	THE SAME AS ABOVE	THE SAME AS ABOVE	THE SAME AS ABOVE	6000	6000
4	THE SAME AS ABOVE	THE SAME AS ABOVE	THE SAME AS ABOVE	THE SAME AS ABOVE	2000	2000
5	THE SAME AS ABOVE	THE SAME AS ABOVE	RIGHT	THE SAME AS ABOVE	9000	8960
6	THE SAME AS ABOVE	THE SAME AS ABOVE	THE SAME AS ABOVE	THE SAME AS ABOVE	6000	6000
7	THE SAME AS ABOVE	THE SAME AS ABOVE	THE SAME AS ABOVE	THE SAME AS ABOVE	2000	2000
8	THE SAME AS ABOVE	THE SAME AS ABOVE	LEFT	THE SAME AS ABOVE	2000	2000
9	THE SAME AS ABOVE	THE SAME AS ABOVE	THE SAME AS ABOVE	THE SAME AS ABOVE	6000	6000
10	THE SAME AS ABOVE	THE SAME AS ABOVE	THE SAME AS ABOVE	THE SAME AS ABOVE	9000	8960

FIG. 4



5/5
FIG. 5



ROTATION SPEED MEASURING MACHINE FOR FLYING GLOBE

The present invention relates to a rotation speed measuring machine for a flying globe such as a golf ball, tennis ball and so on, and more particularly, relates to a rotation speed measuring machine for a flying globe which can measure the rotational speed (spin amount) of a flying globe which has been hit and is flying in the air.

The measurement of the rotational speed of a rotating object without touching it is generally conducted in such a way as a specified light reflection mark is put on the rotating object and the amount of movement of the light reflection mark within a specified time is optically read.

As for a golf ball the same principle holds. For example, in Japanese Patent Application Publication No. Shou 60-21349 Official Gazette, reflection marks are put on two parts of the surface of a golf ball so that the two parts marked have a specified angle θ to the center while a light projecting device and a light receiving device are positioned so as to face the surface on which the golf ball is passing when the ball is hit and flies, and from the time interval t between two electronic signals obtained from the two above-described reflection marks by receiving the reflected light, which comes from the light projecting device, hits the reflection mark and is reflecting, in the light receiving device, the spin amount S of the golf ball is obtained using the formula $S = 60 \times \theta / t \times 360 \text{rpm}$ (the prior embodiment 1).

As for a method similar to this prior embodiment 1, there are Japanese Patent Application Publication No. Shou 60-22302 (the prior embodiment 2), Japanese Patent Application Publication No. Shou 60-22303 (the prior embodiment 3) and so on.

Though the principle is the same as above, it is known that the measurement of the rotational speed of a flying globe is conducted by photographing or using a video camera. That is, a plurality of pictures of a flying globe are taken at specified time intervals, and from the amount of movement of the mark put on a specified position on the flying globe, the rotational speed can be obtained by an operation (the prior embodiment 4).

In the case of the prior embodiment 1 to the prior embodiment 3, however, both the light projecting surface of the light projecting device and the light receiving surface of the light receiving device consist of bundles of optical fibers, and the light projected area and the amount of projected light are limited, so that the effective detected range is no more than 500mm long, 15mm broad, and tens of centimeters high.

Accordingly the rotational speed of a ball immediately after a shot with comparatively less blurring and at a lower position can be measured, but the rotational speed of a ball after this which has been driven high with its route unsettled can't be measured.

When stationary pictures are obtained by photographing or using a video camera as in the prior embodiment 4, if a ball rotates at a high speed, or a ball moves at a high speed, taking a long time to take a picture defaces the picture, so that a flashing device with a short flash time such as a high speed shutter or a micro flash is additionally needed; therefore there is a disadvantage that the entire machine becomes complicated.

It is known that there is a method of taking a stationary picture in a computer by a picture input device and reading the movement amount on the monitor by setting a cursor, and a method of performing a two value process of a picture and making a computer recognize a mark of a specified position on a globe in order to automatically conduct a measurement, but either method has the disadvantages of a complicated program and a lot of time needed for processing data.

In order to increase the precision of measurement of the amount of movement, it is necessary to take a large picture of a ball, but if doing so, the measurement conducting area is reduced, so that the rotation of the ball which has been driven high and is flying in the air, for example, near the highest point is difficult to be measured as in the above.

The amount of spin of a tennis ball in a tennis game is more difficult to be measured since the locus of the ball is further unsettled than that of a golf ball.

Mitigating these conventional circumstances, an object of the present invention is to provide a comparatively simply arranged rotation speed measuring machine for a flying globe which can measure the rotational speed of, for example, a flying globe driven high, with a specified range of space in a field as its measurement conducting area.

In order to attain the above-described object, the present invention is a rotation speed measuring machine for a flying globe measuring the rotational speed of a flying globe by putting a mark having a light reflection rate different from the surface texture on a part of the surface of the flying globe and by detecting the amount of reflected light, and is provided with a light projecting device projecting light on a measurement conducting area which is a space including an expected flying route of the above-described flying globe after the globe has been hit from the ball hitting position, a light receiving device which receives the reflected light from the above-described flying globe flying in the above-described measurement conducting area and which outputs a signal according to the fluctuation of the amount of reflected light, and a rotation speed detecting means detecting the rotational speed of the above-described flying globe based on the output signal from the light receiving device.

In this case a photo diode, phototransistor, or a photo-electric tube are used for the above-described light receiving device as a light sensor, but when the measurement conducting area is darkened or the measurement is conducted at night, it is preferable that a photomultiplier with extremely high reception is used. It is preferable that the above-

described light projecting device is a DC light without light amount fluctuation in itself.

Further it is preferable that the above-described measurement conducting area is equal to or larger than the range in which the above-described flying globe rotates at least twice as it is moving and that the intensity of illumination is at least 100 Lx.

5 As for the case when the rotational speed of a golf ball is measured, it is preferable that an arbitrary area of 5m, which is within 5 to 50m ahead of the light projecting device and which is at the same time within a cylindrical area with a diameter of about 3.6m having the optical axis of the light projecting device as its center, has intensity of illumination of at least 100 Lx.

10 It is said that a golf ball normally flies at a speed of 40 to 60m/s with 2000 to 9000rpm of spin and that the amount of spin is at least about 2000rpm when the golf ball flies at the highest speed of 60m/s.

Meanwhile, when the rotational speed is measured with a light reflection tape on a golf ball, at least one period of fluctuation of the amount of reflected light is required for
15 the measurement.

In order to obtain one period of fluctuation of the amount of reflected light of a golf ball, a golf ball should make one rotation regardless of the shape of a light reflection tape.

20 From the above, the distance in which the golf ball, which flies under the conditions where the largest measuring area is needed, that is, at the highest speed (60m/s) with the smallest amount of spin (2000rpm), flies while the ball rotates once is 1.8m from the following equation.

$$60\text{m/s} \times (1 \times 60/2000) \text{ s} = 1.8\text{m}$$

25 Accordingly, the projection range of the light projecting device should have the distance of at least 1.8m.

When one peak of the light fluctuation is obtained, for example, near the center of the measuring area, it is better if the measuring area is larger in order to measure another peak.

30 If the measuring area is about twice as large as the distance in which a ball moves when the ball makes one rotation, at least two periods of fluctuation of the amount of reflected light can be obtained, therefore the amount of spin of the ball can be measured with high precision even if the peak of the fluctuation of the amount of light is obtained at an arbitrary position of the measuring area.

35 Accordingly if the projection range of the light projecting device has a radius of about 1.8m, that is, a diameter of about 3.6m based on the following equation, the amount of spin of a ball driven by an arbitrary ordinary club can be surely measured.

$$60\text{m/s} \times (2 \times 60/2000) \text{ s} = 3.6\text{m}$$

For example, the light projecting device is positioned at the lower part of a flying area in which a flying globe (for example, a golf ball) is expected to come flying and light is projected from the light projecting device towards the upper space, that is, the sky. In this case, the brightness of the background (in the case of an outdoor area, the sky) does not
 5 change at least abruptly by second or by minute, and is comparatively stable; therefore when a golf ball does not come flying, the detected signal outputted from the light receiving device is stable at a level which can be regarded as almost constant whether the level is high or low.

In this state, when the golf ball with the above-described mark on it comes flying,
 10 the amount of received light (received light level) of the light receiving device changes according to the rotational speed. The change in this case is at an incomparably high speed and large compared to the change of the background, so that the rotational speed of the golf ball is obtained by extracting the amount of change.

In short, even if the background has light fluctuation, the rotational speed of the
 15 golf ball can be measured unless the period of the amount of light fluctuation of the background and the period of the amount of light fluctuation when the golf ball comes flying are the same.

Accordingly, it is suitable if a DC light which does not include fluctuation in the amount of light is used for the light projecting device.

20

In the accompanying drawings:-

Fig. 1 is a typical view for explaining one embodiment of the rotation speed measuring machine of the present invention;

Fig. 2 (A) and Fig. 2 (B) are a side view and a plan view typically showing the
 25 state of the test in which a golf ball is rotated by a motor and the rotational speed is measured by the rotation speed measuring machine of the present invention;

Fig. 3 is a table showing the measurement results of test 1 to test 10;

Fig. 4 is a graph showing the fluctuation of the amount of reflected light reflected from the golf ball in test 11; and

30 Fig. 5 is a graph showing the result of the examination of illumination intensity distribution of an automobile's 85W halogen lamp.

The advantages of the present invention will be more clearly understood by reading each embodiment described below with reference to the attached drawings.

35 A preferable embodiment will be described below with reference to the drawings. Fig. 1 depicts a typical view of the state in which the rotational speed (spin amount) of a flying golf ball B is measured by using the measuring machine of the present invention. In

this case, a mark M having a light reflectance rate different from that of the surface texture of the golf ball B should be put on a part of the surface of the golf ball B, and in this embodiment, the mark M consisting of, for example, black painting is put on so as to cover half the surface of the golf ball B, that is the surface of its hemisphere.

5 This measuring machine is provided with a light projecting device 10 which projects light onto a measurement conducting area A which is a space including a expected flying route of the golf ball which has been hit from the hitting position from, for example, the direction right beneath the measurement conducting area A, a light receiving device 20, for example, with its optic axis facing the vertical direction, in order to receive the diffusing
10 light reflected from the golf ball B flying in the measurement conducting area A, a rotational speed detecting means 30 detecting the rotational speed of the golf ball B based on the output signal outputted from the light receiving device 20 according to the amount of light received, a DC constant voltage power source 12 supplying the light projecting device 10 with electric power, and a high-tension power source circuit 40 supplying the
15 light receiving device 20 with electric power.

In this embodiment, DC light having no fluctuation in the amount of light is used for the light projecting device 10 in order that the fluctuation in the amount of light of the projecting device itself does not interfere with the measurement of the fluctuation in the amount of light resulting from the rotation of the golf ball B. In concrete, the light
20 projecting device 10 consists of sixteen automobile halogen lamps 11 of 85W and the variable DC constant voltage power source 12 of DC 0 to 12V. The direction of each optical axis of each halogen lamp 11 is set and positioned so that the measurement conducting area A has an almost even intensity of illumination.

Meanwhile, the light receiving device 20 consists of a condensing lens having, for
25 example, a diameter of 100mm and a focal distance of 75mm, and a photomultiplier. As for the photomultiplier, for example, R2228 (Trademark) made by Hamamatsu Photonics Co., Ltd. and so on are cited.

The reason why a photomultiplier is used here is that a higher S/N ratio can be obtained by a photomultiplier compared to the case in which a signal amplification is
30 conducted by an amplifier by using a photo diode, phototransistor, a photo-electric tube and so on when the measurement is conducted at night for the purpose of receiving greater fluctuation in the amount of reflected light from the golf ball B than in the amount of light existing in the background.

The rotation speed detecting means 30 is provided with an electric current-
35 voltage conversion circuit 31 converting the output current outputted from the photomultiplier of the light receiving device 20 according to the fluctuation in the amount of light into a voltage signal, an A/D conversion circuit 32 converting the analogue voltage

signal into a digital signal, a digital operation circuit 33 which calculates the voltage fluctuation period T (sec) using the digital signal and which obtains the spin amount S of the golf ball B by conducting the operation of $60(\text{sec}) / T$ (sec) using the data of this period T , and a display device 34 showing the spin amount S . The voltage fluctuation period T is
 5 obtained by the operation recognizing the maximum value of the voltage fluctuation and the operation calculating the time between the maximum values.

In this embodiment, a personal computer is used for the A/D conversion circuit 32, the digital operation circuit 33 and the display 34, and the wave form of the voltage fluctuation is shown on CRT and can be observed. The period T is obtained from the time
 10 between the maximum values of the fluctuation signal on the assumption that the fluctuation of the amount of light existing in the background is small in this embodiment, however, when the amount of light existing in the background fluctuates greatly, unnecessary fluctuation constituent may be eliminated by providing a filter circuit.

Further, the fluctuation period of the amount of the reflected light of the golf ball
 15 B may be obtained from the frequency constituent by suitably designing the light projecting device 10 so that a sufficient length of wave form of the desired fluctuation of the amount of light can be obtained and by conducting Fast Fourier Transform (FFT) of the signal.

In the above-described embodiment, the mark M consisting of black paint is put on the surface of the hemisphere, however, the method of partially changing the reflectance
 20 rate is not limited to that in this embodiment. For example, the painting classification part may be divided into quarters, that is the surface of the golf ball B may be divided into quarter segments and the light reflection mark M may be put on the surfaces of two divided quarter segments facing each other, and the color of the mark is not limited to black.

In short, any method may be suitable if the amount of reflected light changes
 25 according to the rotation of the golf ball B , and the method is not particularly limited if only the rotational speed of the ball can be obtained from the change of the amount of reflected light. When the surface is divided into quarter segments for marking, the fluctuation period of the amount of light for the rotational speed of the ball becomes $1/2$ of that in the case when the surface is divided into halves, therefore when the fluctuation of the amount of
 30 light exists in the background or in the projected light itself, the separation may be easier by making the fluctuation period of the amount of light in the background or in the projected light different from the fluctuation period of the amount of reflected light from the rotation of the ball.

In the above-described embodiment, the light projecting device 10 and the light
 35 receiving device 20 are positioned right beneath the measurement conducting area A in order to particularly measure the back spin of the golf ball B , however, the direction of each optical axis of the light projecting device 10 and the light receiving device 20 is not

limited to this position and can be suitably set in consideration of the direction of the rotation axis of the spin to be measured and the reflected light from the background of the place for conducting measurement.

5 The measurement of the spin amount (rotation speed) by using this rotation speed measuring machine was conducted by creating the simulated state in which the above-described golf ball B is rotating in the air, and the description of the measurement with reference to Fig. 2 (A) and Fig. 2 (B) will be as follows. Fig. 2 (A) is a typical side view of the scene of the test and Fig. 2 (B) is a typical plan view of the scene of the test.

10 First, the golf ball B with its half of the surface painted black as described above is attached on the rotation shaft of a variable motor 50 and set at the position 850mm above the ground while the light receiving device 20 is set at a position 30m apart from the golf ball B in such a way as the optical axis of received light passes the center of the rotation of the golf ball B and is horizontal at the same time.

15 Since in this test the optical axis of the received light of the light receiving device 20 is in the horizontal direction as described above, there is a fear of light reflecting from the ground coming out as noises when the light projecting device 10 is positioned near the light receiving device 20, so that a dry cell type of a penlight is used for the light source and the light is projected on the golf ball B from the lower position at an angle.

20 This test is conducted at night in order to obtain a greater amount of fluctuation of the light from the golf ball B than the amount of light existing in the background and the intensity of illumination near the golf ball B is measured with an illuminometer 51. The measurement was conducted by setting the golf ball B at each of the (mid) position which is on the optical axis of the received light of the light receiving device 20, and at the (right) position and the (left) position which are respectively and laterally 2.5m away from the same optical axis of the received light as Fig. 2 (B) depicts, assuming an actual case when
25 the golf ball B rotates as it is flying in the measurement conducting area. The rotational speed of the golf ball B by the motor 10 is respectively 2000rpm, 6000rpm, and 9000rpm at each position.

(Test 1)

30 The golf ball B was rotated by the motor 50 at 9000rpm at the (mid) position on the optical axis of the received light of the light receiving device 20 with 70 Lx of intensity of illumination of the area surrounding the golf ball B. After the amount of reflected light was detected at the light receiving device 20 and the output signal was taken in the rotation speed detecting means 30, the fluctuation period was to be read by observing the wave
35 forms, but the fluctuation period could not be measured since the wave forms were incomplete.

(Test 2)

When intensity of illumination of the area surrounding the golf ball B was changed to be 100 Lx with other things being under the same conditions as in Test 1 and the measurement was conducted, the wave form of 0.0067sec period was observed. Accordingly, the measured value in this case was 8960rpm which was a little lower than the
5 actual rotational speed.

(Test 3)

When the golf ball B was rotated by the motor 50 at 6000rpm with 100 Lx of intensity of illumination of the area surrounding the golf ball B and with the other things being under the same conditions as in Test 1, the wave form of 0.010sec period was
10 observed and by this 6000rpm which was the same as the actual rotational speed was measured.

(Test 4)

When the golf ball B was rotated by the motor 50 at 2000rpm with 100 Lx of intensity of illumination of the area surrounding the golf ball B and with the other things
15 being under the same conditions as in Test 1, the wave form of 0.030sec period was observed. By this, 2000rpm which was the same as the actual rotational speed was measured.

(Test 5)

The golf ball B was rotated by the motor 50 at 9000rpm at the (right) position
20 2.5m away in the right direction from the optical axis of the received light of the light receiving device 20 with 100 Lx intensity of the illumination of the surrounding area. When the amount of reflected light was detected at the light receiving device 20 and the output signal was taken in the rotation speed detecting means 30 to observe the wave form, the wave form of 0.0067sec period was observed. Accordingly, the measured value of this
25 case was 8960rpm which was a little lower than the actual rotational speed.

(Test 6)

When the golf ball B was rotated by the motor 50 at 6000rpm with the other things being under the same conditions as in Test 5, the wave form of 0.010sec period was
30 observed and by this 6000rpm which was the same as the actual rotational speed was measured.

(Test 7)

The golf ball B was rotated by the motor 50 at 2000rpm with the other things being under the same conditions as in Test 5, the wave form of 0.030sec period was
35 observed and by this 2000rpm which was the same as the actual rotational speed was measured.

(Test 8)

The golf ball B was rotated by the motor 50 at 2000rpm at the (left) position

2.5m away in the left direction from the optical axis of the received light of the light receiving device 20 with 100 Lx of intensity of illumination of the surrounding area. When the amount of reflected light was detected at the light receiving device 20 and the output signal was taken in the rotation speed detecting means 30 to observe the wave form, the wave form of 0.030sec period was observed and by this 2000rpm which was the same as the actual rotational speed was measured.

(Test 9)

When the golf ball B was rotated by the motor 50 at 6000rpm with the other things being under the same conditions as in Test 8, the wave form of 0.010sec period was observed and by this 6000rpm which was the same as the actual rotational speed was measured.

(Test 10)

When the golf ball B was rotated by the motor 50 at 9000rpm with other things being under the same conditions, the wave form of 0.0067sec period was observed. Accordingly, the measured value of this case was 8960rpm which was a little lower than the actual rotational speed.

The results of these tests show that when the intensity of illumination of the area around the ball (flying globe) is at least 100 Lx the output signal can be steadily obtained from the light receiving device according to the spin amount (rotational speed) even if the ball was away from the optical axis of the received light of the light receiving device. For reference, the measurement results of the above-described Test 1 to 10 are shown in Fig. 3.

Then test 11 in which the golf ball B was actually driven in the air and the amount of spin near the highest point on the flying locus was measured will be described in the following.

(Test 11)

The surfaces of two divided quarter segments of the golf ball were painted black in order that the surfaces of two divided quarter segments facing each other of four divided quarter segments have a light reflection rate different from the light reflection rate of the texture surface. Accordingly, when this golf ball makes one rotation, two periods of fluctuation of the amount of light can be obtained.

Then this golf ball was driven into the air by the driver of the golf club attached at the swing robot at a starting speed of about 60m/s, at a driving angle of about 11 degrees, with starting spin amounting to about 3300rpm.

Meanwhile, the light projecting device 10 was positioned so that the amount of spin of the golf ball at the position of 140m ahead of the driving position was able to be measured. The height of the flight of the golf ball at this position was about 30m.

Two lines of eight automobile halogen lamps placed at intervals of 300mm were

provided parallel to each other (a total of sixteen lamps) as this light projecting device 10, and with the optical axis of each lamp being vertically adjusted, 12V was applied to each lamp by the DC constant-voltage power supply.

5 The amount of light fluctuation of the reflected light reflected from the golf ball is shown in Fig. 4. This drawing shows that it took 0.05762 seconds for the golf ball to rotate three times.

Accordingly, the amount of spin of the golf ball at this time can be approximately computed to be about 3120rpm from the following equation.

$$60 / (0.05762 / 3) = \text{about } 3120\text{rpm}$$

10 When the golf ball passes the measurement conducting area at a speed of 60m/s, the distance in which the golf ball moves while the golf ball rotates three times can be approximately computed to be about 3.6m from the following equation.

$$0.05762 \times 60 = \text{about } 3.6\text{m}$$

15 In other words, if the light projecting device 10 is suitably set so that the distance of the measurement conducting area is at least 3.6m, the fluctuation in the amount of light of the golf ball after rotating three times can be obtained, so that it can be understood that the amount of spin of the golf ball can be measured with high precision.

20 In this measuring device, a measurement was able to be conducted even when only eight lamps out of sixteen lamps arranging the light projecting device 10 were lit by lighting every other lamp out of the lamps placed in each line.

In short, in this measuring device, the amount of spin of the golf ball can be measured even by using an arbitrary number of lights out of sixteen lights if the golf ball passes so as to cross the optical axis.

25 For reference, the examination result of the illumination intensity distribution of an automobile's 85W halogen lamp at the position 30m ahead of the automobile's 85W halogen lamp is shown in Fig. 5.

30 As described above, by the present invention the following effects were obtained. That is, the rotational speed of the ball actually flying in the air at around the highest point of its flight locus can be measured by the invention in Claim 1 which is provided with the light projecting device projecting light onto the measurement conducting area of the space including the expected flying route of the flying globe (for example, a golf ball) which has been hit from the ball hitting position, the light receiving device which receives reflected light from the flying globe flying in the measurement conducting area and which outputs a signal according to the degree of fluctuation of the reflected light, and the rotation speed
35 detecting means detecting the rotational speed of the above-described flying globe based on the output signal from the light receiving device.

By the invention in Claim 2 in which a photomultiplier is used in the above-

described light receiving device, a high S/N ratio can be obtained, so that it is especially suitable for a measurement which is conducted at night.

5 By the invention in Claim 3 in which the above-described light projecting device is a DC light, no light fluctuation from the light projecting device exists, so that the same amount of noise can be reduced.

By the invention in Claim 4 in which the above-described measurement conducting area is equal to or larger than the range in which the above-described flying globe rotates at least twice as it is moving, the fluctuation frequency caused by the light reflection mark of the flying globe can be obtained with higher precision.

10 Meanwhile, by the invention in Claim 5 in which the intensity of illumination of the above-described measurement conducting area is 100 Lx or more, an output signal can be steadily obtained according to the rotational speed of the ball even if the ball is away from the optical axis of the received light of the light receiving device.

15 Regarding each invention described above, by the invention in Claim 6 in which an arbitrary area of 5m, which is within 5 to 50m ahead of the light projecting device and at the same time within the cylindrical area with a diameter of about 3.6m having the optical axis of the above-described light projecting device as its center, has 100 Lx of intensity of illumination, at least 2 periods of the light amount fluctuation wave forms can be surely observed, therefore the rotational speed of a flying globe can be measured more precisely.

CLAIMS

1. A rotation speed measuring machine for a flying globe measuring the rotational speed of a flying globe by putting a mark with a light reflectance rate different from the reflectance rate of the surface texture on a part of the surface of the flying globe and by detecting the amount of reflection light of the mark, comprising:
 - a light projecting device projecting light on a measurement conducting area which is a space including an expected flying route of the above-described flying globe after the globe has been hit from the ball hitting position;
 - a light receiving device which receives the reflection light from the above-described flying globe flying in the above-described measurement conducting area and which outputs a signal according to the fluctuation of the reflection light amount; and
 - a rotation speed detecting means detecting the rotational speed of the above-described flying globe based on an output signal from said light receiving device.
2. A rotation speed measuring machine for a flying globe according to Claim 1, wherein a photomultiplier is used in said light receiving device.
3. A rotation speed measuring machine for a flying globe according to Claim 1, wherein said light projecting device is provided with a DC light.
4. A rotation speed measuring machine for a flying globe according to Claim 1, wherein the above-described measurement conducting area is set so as to be equal to or larger than the range in which the above-described flying globe rotates at least twice as it is moving.
5. A rotation speed measuring machine for a flying globe according to Claim 1 or Claim 4, wherein the intensity of illumination of the above-described measurement conducting area is at least 100 Lx.
6. A rotation speed measuring machine for a flying globe according to Claim 1, Claim 3, Claim 4, or Claim 5, wherein an arbitrary area of 5m, which is within 5 to 50m ahead of said light projecting device and which is at the same time within a cylindrical area with a diameter of 3.6m having the optical axis of said light projecting device as its center, has intensity of illumination of at least 100 Lx.



Application No: GB 9622562.8
Claims searched: All

Examiner: Bob Clark
Date of search: 25 February 1997

Patents Act 1977
Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:
UK Cl (Ed.O): G1A (AAJX, AEAX, AEDX, AEJX, AEX)
Int Cl (Ed.6): A63B 69/00, 69/36, 69/38; G01P 3/36, 3/38, 3/40, 3/64, 3/68; G01S 11/12
Other: Online database: WPI

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
X	GB2288662 A (SUMITOMO) Whole document	1, 3, 5
X	EP0704715 A1 (ACUSHNET) pages 2 and 3	1, 3, 5
X	EP0554978 A2 (ACUSHNET) Whole document	1, 2, 3, 5
X	US5226660 (CURCHOD) Column 6 line 17 to column 7 line 32	1, 3
X	US4158853 (SULLIVAN et al.) Whole document	1, 5
X	US3630601 (LEHOVEC) Whole document	1, 4, 5

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.